



# DCP-100

## Dual Cold Plate

PRECISION FIXTURE FOR ALL 4 DCP MODES HAS ACCESSORIES  
FOR OTHER THERMAL MEASUREMENTS

### DESCRIPTION

The DCP-100 is specifically designed for validating detailed thermal models according to the four DCP modes outlined by European DELPHI/SEED projects. Available accessories include a magnetically-positioned pressure plate with insulated conduction plate for use in making DCP4 mode measurements on test samples configured with copper plates soldered to test device leads. Also available is an accessory unit for making measurements in accordance with EIA/JEDEC JESD51-8 Integrated Circuit Thermal test Method Environmental Conditions - Junction-to-Board ( $\theta_{JB}$ ). The DCP-100 is a flexible fixture that can be augmented by customer-designed elements for making other type of thermal measurements.

The basic DCP-100 unit comes equipped with dual cold plates, one on the top and one on the bottom, that have been specifically designed to minimize thermal gradients across the interface surface. Separate connections to and flow meters for each cold plate allow the user to maintain the same temperature for both plates or to feed liquid at different temperatures to each plate. The cold plates are 12.7 cm (5") on a side, large enough to accommodate the largest semiconductor device packages, have a Type-T thermocouple embedded 12.7 microns (0.005") below the center of the interface circuit. Each cold plate is mounted on an FR4 material to thermally insulate it from the metal components making up the rest of the DCP-100.

A compressed air cylinder lowers and raises the top cold plate and, with the unit's built-in regulator and pressure monitor, allows the plate to be applied to the test sample with a controlled and repeatable amount of force. Both the top and bottom plate mechanisms are gimbaled to insure that the two plate interface surfaces are parallel to each other. A 12-channel thermocouple scanner is built-in to the base unit to monitor the temperature of the cold plates and up to 10 other user-defined points. The scanner can be interfaced to a computer and is supplied with monitoring software.



Please go to next page.

**TEA**  
**Thermal Engineering Associates, Inc.**

**612 National Ave., Mountain View, CA 94043-2222 USA**  
**Phone: 650-961-5900 Email: info@thermegr.com**

Specifications subject to change without notice.

Printed in USA.

020612

## FEATURES

- **Self-contained for easy setup and operation**
- **Alignment pins simplify positioning of interchangeable parts**
- **Flexible design easily adapted to alternative applications**
- **Integrated thermocouple scanner has computer interface to simplify data collection**
- **Digital display for air pressure allows for precise force application**
- **Safety interlocked covers prevents operator injury**

## SPECIFICATIONS

<b>Compressed Air:</b>	<b>Input Pressure</b>	<b>40 psi nominal (60 psi max)</b>
	<b>Connectors</b>	<b>1/4" OD, Quick Connect</b>
<b>Coolant:</b>	<b>Liquid</b>	<b>Mineral-free water or glycol solution</b>
	<b>Flow Rate</b>	<b>45.5 lph (12 gph)</b>
	<b>Connectors</b>	<b>1/4" OD, Quick Connect</b>
<b>Thermocouple:</b>	<b>Type</b>	<b>Type-T</b>
	<b>Quantity</b>	<b>1 for each cold plate</b>
	<b>Connectors</b>	<b>Miniature Plugs (Omega NMP-T or equivalent)</b>
<b>Thermocouple Scanner:</b>	<b>Number of Channels</b>	<b>12</b>
	<b>Type</b>	<b>Type-T</b>
<b>(Applies to DCP-100 only)</b>	<b>Input Connectors</b>	<b>Miniature Jacks</b>
	<b>Display</b>	<b>LCD Digital</b>
	<b>Outputs</b>	<b>Printer (Centronics-compatible parallel) Serial (RS-232C for computer interface)</b>
<b>Size:</b>	<b>Height</b>	<b>53.3 cm (21")</b>
	<b>Width</b>	<b>43.2 cm (17")</b>
	<b>Depth</b>	<b>25.4 cm (10")</b>
<b>Power:</b>	<b>Voltage</b>	<b>100,120, 220, 240 VAC</b>
	<b>Frequency</b>	<b>50/60 Hz</b>
	<b>Current</b>	<b>1 A</b>

## ORDERING INFORMATION

<b>Model Number</b>	<b>Description</b>
<b>DCP-100</b>	<b>Base Unit</b>
<b>DCP-100-01</b>	<b>Base Unit without thermocouple scanner</b> (Customer supplies thermocouple instrumentation)
<b>DCP-100-02</b>	<b>DCP4 Mode Pressure Pins and Insulated Plate</b> Includes 6 magnetized pressure pins
<b>DCP-100-03A</b>	<b><math>\theta_{JB}</math> Test Section</b> Provides interchangeable parts for making measurements in accordance with JESD51-8; supplied with appropriate thermocouples; accepts up to 30 mm square packages
<b>DCP-100-03B</b>	<b><math>\theta_{JB}</math> Test Section</b> Provides interchangeable parts for making measurements in accordance with JESD51-8; supplied with appropriate thermocouples; accepts up to 52 mm square packages
<b>DCP-100-08</b>	<b>Conductive Package Posts</b> Custom designed for specific package style; includes thermocouple mounted under package interface surface (Consult Factory for details)
<b>DCP-100-09</b>	<b>Insulating Package Posts</b> Custom designed for specific package style (Consult Factory for details)
<b>DCP-100-99</b>	<b>System Cart</b> Self-contained wheeled unit for mounting DCP-100 on top with integrated thermoelectric chiller, air compressor, and master Power Main switch below; has drawer for storing optional components.